



Versatility



Document encryption and a 10-digit numeric key pad for confidential print jobs

New “show me” messaging screen for easy navigation

Convenient front USB direct interface for convenient PDF printing.

Easily customized to meet every business need

Lexmark W840, W840n, W840dn	
Part Number	Canada 25A0075 (W840), 25A0001 (W840n), 25A0076 (W840dn)
Technology	A3 monochrome laser
Speed	Up to 50 ppm
Resolution	2400 image quality, 1200 x 1200 dpi
Time to First Page	As fast as 6.8 seconds
Processor	625 MHz
Memory (std./max.)	256MB/768MB
Connectivity	USB and IEEE 1284 Parallel standard on all models 10/100bTX standard (integral) on W840n and W840dn. Models W840, W840n and W840dn have 2 open Internal Solution Slots Optional: Serial/Parallel, MarkNet N8000 Series Internal Print Servers, Coax/Twinax, N4000e external print server
Operating Systems	Windows XP, 2000, Me, 98, 95, NT 4.0, UNIX, Linux; Mac OS For a complete List, visit www.lexmark.com
Emulations	PostScript 3 emulation standard, PCL 6 emulation, PPDS Migration Tool, PDF V1.5
Fonts	PostScript 3 emulation, 158 scalable PCL 6 emulation, 94 scalable – 2 bitmapped PPDS 39 scalable fonts – 5 bitmapped
Paper Capacity Standard (in/out) Maximum (in/out)	1,100/500 (100 + 500 + 500/500) 5,100/3,800 (100 + 500 + 500 + 500 + 2,000 + 2,000/300 + 500 + 3000)
Paper Options	Input: 2,000-sheet high capacity feeder, 100-envelope feeder Output: 3,500-sheet finisher (multipositioning stapling, up to 50 sheets per set; three or two hole available RPQ; offsetting) Other: Duplex unit
Paper Sources Standard (in/out) Maximum (in/out)	3/1 6/3
Media Types	Plain paper, bond, envelopes, card stock, transparencies, and paper labels
Media Sizes	Letter, legal, A3, A4, A5, JIS, B4, B5, executive, statement, folio, universal, envelopes (COM10, 7-3/4, DL, C4 and other)
Media Weights	Plain paper: 16 to 28 lb (60 to 105 g/m ²); Card stock: up to 90 lb index (163 g/m ²)
Size/Weight	W840, W840n: 24" x 20.5" x 18.7" (W x D x H) (616 mm x 520 mm x 475 mm) 100.5 lb (46 kg) W840dn: 36" x 24" x 22" (W x D x H) (929 mm x 615 mm x 517 mm) 107.8 lb (49 kg)
Acoustics	55 dBA printing; 28 dBA idle
Supplies¹	Ships with: 30,000-page Print Cartridge + 60,000-page Photoconductor Kit
Duty Cycle	Up to 300,000 pages per month
Warranty	1-year LexOnSite

Functionality and versatility

Print Cartridges ¹	Part No.
30,000-page Print Cartridge	W84020H
60,000-page Photoconductor Kit	W84030H
Media	
Transparencies (Letter, 50 sheets)	70X7240
Other	
Staple Cartridges	25A0013
Paper Handling Options	
High Capacity Feeder	25A0025
Duplex Unit	25A0015
Finisher 2/3-hole	25A0030
2X500-Sheet Drawer	25A0010
850 + 1150-Sheet Dual Input	25A0020
3500-Sheet Finisher	25A0030
Memory Options	
128MB DDR-DRAM	13N1523
256MB DDR-DRAM	13N1524
512MB DDR-DRAM	13N1526
32MB Flash CARD	1021208
64MB Flash CARD	1021209
20 + GB Hard Disk with Adapter	12N1262
Font Options	
Simplified Chinese Font DIMM	1021241
Traditional Chinese Font DIMM	1021242
Korean Font DIMM	1021240
Japanese Font DIMM	1021243

Optra Forms Solutions	Part No.
Optra Forms Card	25A0035
Optra Forms Software	11N0040
Optra Forms Director	11N0052
Optra Forms Manager	11N0056
Internal Print Servers	
MarkNet N8000 Ethernet 10/100BaseTX	14S0230
MarkNet N8020 Gigabit Ethernet 10BaseT/2	14S0200
MarkNet N8050 802.11g Wireless	14S0165
Internal Fiber Optic Print Servers	
MarkNet N8030 100Base FX T Connector	14S0220
External Print Servers	
N4000e External Print Server Ethernet 10/100BaseTX – 1-port	14T0030
MarkNet X2011e Ethernet 10/100BaseTX – 1-Port	46D0060
MarkNet X2012e Ethernet 10/100BaseTX/10Base2 – 1-Port	46D0040
MarkNet X2031e Ethernet 10/100BaseTX – 3-Port	46D0020
MarkNet X2030t Token-Ring – 3-Port	46D0000
Interface Card	
USB/Parallel 1284-C Interface Card	1021091
Adapters	
External Serial Adapter	1368705
Coax/Twinax Adapter for SCS	14S0240
802.11g Wireless Print Adapter ²	1010042

Cables	Part No.
3-Meter Parallel 1284-C Cable	43H5171
10-Foot Parallel Cable	1329605
2-Meter USB Cable	12A2405
50-Foot Serial Cable	1038693



¹Yield is based on approximately 5% print coverage

²Requires network connectivity

³Customer testing required to ensure compatibility